

according to Regulation (EC) No 1907/2006

# Asplit® 876 Hardener

Revision date: 19.04.2017 Product code: 00359-1210 Page 1 of 9

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Asplit® 876 Hardener

Art.-No.

592 0615. 592 0615M

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Hardener

### 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflaechenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50 Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

**1.4. Emergency telephone** INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories:

Substance or mixture corrosive to metals: Met. Corr. 1

Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Corr. 1B

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

May be corrosive to metals.

Harmful if swallowed or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

# Regulation (EC) No. 1272/2008

# Hazard components for labelling

Benzyl alcohol

Formaldehyde polymer with 1,3-benzenedimethanamine and phenol

Xylylenediamine Triethylenetetramine

Signal word: Danger

Pictograms:





### **Hazard statements**

H290 May be corrosive to metals.



according to Regulation (EC) No 1907/2006

# Asplit® 876 Hardener

Revision date: 19.04.2017 Product code: 00359-1210 Page 2 of 9

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P330 Rinse mouth.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P273 Avoid release to the environment.

### 2.3. Other hazards

Not known.

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
100-51-6	Benzyl alcohol			< 50 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4; H302 H332			
57214-10-5	Formaldehyde polymer with 1,3-benzenedimethanamine and phenol			> 25 %
	500-137-0		01-2119966906-20	
	Skin Corr. 1C, Skin Sens. 1, Aquatic Chronic 3; H314 H317 H412			
1477-55-0	Xylylenediamine			< 20 %
	216-032-5		01-2119480150-50	
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H302 H332 H314 H317 H412 EUH071			
112-24-3	Triethylenetetramine			< 10 %
	203-950-6	612-059-00-5		
	Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, Skin Sens. 1, Aquatic Chronic 3; H302 H312 H314 H317 H412			

Full text of H and EUH statements: see section 16.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

### **General information**

Remove contaminated soaked clothing immediately.

Consult a physician.

Take away from danger area and lay down affected person.



according to Regulation (EC) No 1907/2006

# Asplit® 876 Hardener

Revision date: 19.04.2017 Product code: 00359-1210 Page 3 of 9

#### After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

#### After contact with skin

In case of contact with skin wash off immediately with plenty of water.

Consult a doctor if skin irritation persists.

#### After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.

#### After ingestion

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Never give anything by mouth to an unconscious person.

Induce vomiting only upon the advice of a physician.

Summon a doctor immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Harmful if swallowed or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

### **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

# Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

# Unsuitable extinguishing media

Full water jet.

# 5.2. Special hazards arising from the substance or mixture

Fire may produce:

carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx)

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

### Additional information

Do not release chemically contaminated water into drains, soil or surface waters. Sufficient measures must be taken to retain water used for extinguishing.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Ensure adequate ventilation.

Use personal protective clothing.

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

Do not discharge into the subsoil/soil.

#### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.





according to Regulation (EC) No 1907/2006

# Asplit® 876 Hardener

Revision date: 19.04.2017 Product code: 00359-1210 Page 4 of 9

Do not use metal containers.

#### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

### **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed.

Avoid contact with the skin and the eyes.

Use only in thoroughly ventilated areas.

#### Advice on protection against fire and explosion

No special protective measures against fire required.

#### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Do not use metal containers.

# Advice on storage compatibility

Incompatible with acids.

### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

Hardener

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Additional advice on limit values

No data available.

# 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

#### Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

#### Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

#### Hand protection

Chemical protective gloves made of nitrile, nitrile/cotton, butyl or neoprene, with a minimum thickness of 0.7 mm. permeation time of approx. 480 minutes.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Pls. find examples in the protective gloves database under: http://bestglove.com/site/chemrest/



according to Regulation (EC) No 1907/2006

# Asplit® 876 Hardener

Revision date: 19.04.2017 Product code: 00359-1210 Page 5 of 9

#### Skin protection

Long sleeved clothing (EN 368).

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Yellowish
Odour: Amine like

Test method

pH-Value: > 11

Changes in the physical state

Initial boiling point and boiling range:  $> 107 \, ^{\circ}\text{C}$  Flash point:  $> 112 \, ^{\circ}\text{C}$  Lower explosion limits: n.d.

Upper explosion limits:

Ignition temperature: n.d.

Vapour pressure: n.d.

Density (at 21 °C): 1,1 g/cm³

Water solubility: Slightly miscible (at 20 °C)

Viscosity / dynamic: 200 - 350 mPa·s

(at 25 °C)

### 9.2. Other information

No data available.

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No decomposition if stored and applied as directed.

### 10.2. Chemical stability

Stable under normal conditions.

# 10.3. Possibility of hazardous reactions

Reactions with strong acids.

Gives off hydrogen by reaction with metals.

### 10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

#### 10.5. Incompatible materials

Acids.

Hydrogen, by reaction with metals.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Revision No: 1,4 GB - EN Print date: 19.04.2017





according to Regulation (EC) No 1907/2006

# Asplit® 876 Hardener

Revision date: 19.04.2017 Product code: 00359-1210 Page 6 of 9

#### **Acute toxicity**

Harmful if swallowed or if inhaled. LD50/oral/rat: 1230 mg/kg

#### Irritation and corrosivity

Causes severe skin burns and eye damage.

#### Sensitising effects

May cause an allergic skin reaction. (Formaldehyde polymer with 1,3-benzenedimethanamine and phenol;

Xylylenediamine; Triethylenetetramine)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### **Practical experience**

#### Other observations

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecological data are not available.

Harmful to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### 12.6. Other adverse effects

Hazardous water pollutant.

#### **Further information**

Do not flush into surface water or sanitary sewer system.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

### Waste disposal number of waste from residues/unused products



according to Regulation (EC) No 1907/2006

# Asplit® 876 Hardener

Revision date: 19.04.2017 Product code: 00359-1210 Page 7 of 9

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

#### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken

for reuse.

### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

**14.1. UN number:** UN 2735

**14.2. UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Formaldehyde polymer with

1,3-benzenedimethanamine and phenol)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Classification code: C7

Limited quantity: 1 L / 30 kg

Excepted quantity: E2
Transport category: 2
Hazard No: 80
Tunnel restriction code: E

Inland waterways transport (ADN)

<u>14.1. UN number:</u> UN 2735

**14.2. UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Formaldehyde polymer with

1,3-benzenedimethanamine and phenol)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Classification code: C7
Limited quantity: 1 L / 30 kg
Excepted quantity: E2

Marine transport (IMDG)

**14.1. UN number:** UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Formaldehyde polymer with

1,3-benzenedimethanamine and phenol)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



according to Regulation (EC) No 1907/2006

### Asplit® 876 Hardener

Revision date: 19.04.2017 Product code: 00359-1210 Page 8 of 9



Marine pollutant:

Limited quantity:

Excepted quantity:

EmS:

No

1 L / 30 kg

E2

EnS:

F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 2735

14.2. UN proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Formaldehyde polymer with

1,3-benzenedimethanamine and phenol)

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8



Limited quantity Passenger: 0.5 L
Passenger LQ: Y840
Excepted quantity: E2

IATA-packing instructions - Passenger:851IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:855IATA-max. quantity - Cargo:30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

#### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 0 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

# **SECTION 16: Other information**





according to Regulation (EC) No 1907/2006

# Asplit® 876 Hardener

Product code: 00359-1210 Revision date: 19.04.2017 Page 9 of 9

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

#### Relevant H and EUH statements (number and full text)

H290 May be corrosive to metals. H302

Harmful if swallowed.

H302+H332 Harmful if swallowed or if inhaled. Harmful in contact with skin. H312

H314 Causes severe skin burns and eve damage.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

Harmful to aquatic life with long lasting effects. H412

Corrosive to the respiratory tract. EUH071

#### **Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)