

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

TIP TOP COROPUR AKTIVATOR A-1949

#### Art.-No.

580 0676, 580 0700, 580 0717, 580 0730, 580 0740, 580 1510 (Coropur Non Abrassiv)

580 0690, 580 0724, 580 1527 (Coropur Non Abrassiv LS)

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Activator

### 1.3. Details of the supplier of the safety data sheet

Company name: TIP TOP Oberflächenschutz Elbe GmbH

Street: Heuweg 4

Place: D-06886 Wittenberg

Telephone: +49(0)3491/635-50

Telefax: +49(0)3491/635-552

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

### 1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24  
24

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Flammable liquid: Flam. Liq. 3

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Flammable liquid and vapour.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Hazard components for labelling

Bis[2-[2-(1-methylethyl)-3-oxazolindinyl]ethyl] hexan-1,2-diylbiscarbamate

n-Butyl acetate

Signal word:

Warning

Pictograms:



#### Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take precautionary measures against static discharge.



P260	Do not breathe vapour.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P501	Dispose of contents/container to in accordance with local and national regulations.

**Special labelling of certain mixtures**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3. Other hazards**

Vapours may form explosive mixture with air.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Polyoxazolidine

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
59719-67-4	Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl] hexan-1,2-diylbiscarbamate			50 - 100 %
	261-879-6		01-2119983487-19	
	Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H319 H317 H411			
123-86-4	n-Butyl acetate			25 - 50 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

If you feel unwell, seek medical advice.

Take away from danger area and lay down affected person.

Never give anything by mouth to an unconscious person.

In case of the person being unconscious put him/her in a stable side position.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

Refer for medical treatment.

If patient is not breathing, apply artificial respiration.

**After contact with skin**

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

Do not use solvents or thinners.

**After contact with eyes**

Remove contact lens.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Seek medical treatment by eye specialist.



#### **After ingestion**

Do not induce vomiting.

Rinse mouth.

Never give anything by mouth to an unconscious person.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

---

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

##### **Unsuitable extinguishing media**

Full water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>).

#### **5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.

Protective suit.

#### **Additional information**

Cool containers at risk with water spray jet.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Vapours are heavier than air and spread along ground.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

Inform competent authority about release into the sewage, ground or into waters.

#### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

---

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Keep container tightly closed.

Keep a good ventilation and air-exhaust at the place of work.

Vapours are heavier than air and spread along ground.



Avoid contact with the skin and the eyes.  
When using do not eat, drink or smoke.

**Advice on protection against fire and explosion**

Keep away from heat and sources of ignition.  
Do not smoke.  
Take precautionary measures against static discharges.  
Use only explosion-proof equipment.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.  
Pay attention to anti-explosion protection rules.  
Protect from heat and direct solar radiation.  
Storage temperature between 15°C to 30°C  
Do not empty container under pressure. No pressure tank!  
Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

**Advice on storage compatibility**

Incompatible with:  
Oxidizing agents  
Acids and bases.

**Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

**7.3. Specific end use(s)**

Activator

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL

**Additional advice on limit values**

Splash protection:  
Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0,7 mm, permeation resistance (wear duration) > 60 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

**8.2. Exposure controls**

**Appropriate engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Protective and hygiene measures**

Do not inhale vapours.  
Wash hands before breaks and immediately after handling the product.  
When using do not eat, drink or smoke.  
Treat subsequently with skin cream.  
Remove and wash contaminated clothing before re-use.

**Eye/face protection**

Tightly fitting goggles (EN 166).  
Eye wash bottle with pure water (EN 15154).

**Hand protection**

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.  
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.  
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.



**Skin protection**

Long sleeved clothing (EN 368).

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	Various
Odour:	characteristic

**Changes in the physical state**

Flash point:	27 °C	DIN 53213
Lower explosion limits:	1,9 vol. %	
Upper explosion limits:	6,1 vol. %	
Ignition temperature:	370 °C	
Vapour pressure: (at 20 °C)	5,27 hPa	
Density (at 20 °C):	0,99 g/cm <sup>3</sup>	
Water solubility: (at 20 °C)	Immiscible	
Viscosity / kinematic: (at 40 °C)	< 20,5 mm <sup>2</sup> /s	
Flow time:	14 s	4 DIN 53211
Solvent content:	41 %	

**9.2. Other information**

No data available.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

No decomposition if stored and applied as directed.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

Reactions with acids, alkalies and oxidizing agents

**10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.  
Heating can release vapours which can be ignited.  
Vapour/air-mixtures are explosive at intense warming.

**10.5. Incompatible materials**

Strong oxidizing agents  
Strong acids and strong bases

**10.6. Hazardous decomposition products**

Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>).

**SECTION 11: Toxicological information**

**11.1. Information on toxicological effects**

**Acute toxicity**

Based on available data, the classification criteria are not met.  
No toxicological data available.

**Irritation and corrosivity**

Causes serious eye irritation.  
Skin irritation: Not classified.



### **Sensitising effects**

May cause an allergic skin reaction. (Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl]hexan-1,2-diylbiscarbamate)

### **STOT-single exposure**

May cause drowsiness or dizziness. (n-Butyl acetate)

### **Severe effects after repeated or prolonged exposure**

Repeated exposure may cause skin dryness or cracking.

### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### **Additional information on tests**

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

### **Practical experience**

#### **Other observations**

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Inhalation of high concentrations may cause injuries to liver, kidneys and central nervous system.

A longer or repeated contact may lead to irritation of eyes and mucous membranes.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

---

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Ecological data are not available.

### **12.2. Persistence and degradability**

No data available.

### **12.3. Bioaccumulative potential**

No data available.

### **12.4. Mobility in soil**

No data available.

### **12.5. Results of PBT and vPvB assessment**

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### **12.6. Other adverse effects**

Low hazard to waters.

### **Further information**

Do not flush into surface water or sanitary sewer system.

---

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

#### **Advice on disposal**

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

#### **Waste disposal number of waste from residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances  
Classified as hazardous waste.

#### **Contaminated packaging**

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint related material  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L / 30 kg  
 Excepted quantity: E1  
 Transport category: 3  
 Hazard No: 30  
 Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint related material  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 5 L / 30 kg  
 Excepted quantity: E1

**Marine transport (IMDG)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint related material (Bis[2-[2-(1-methylethyl)-3-oxazolidinyl]ethyl]hexane-1,2-diylbiscarbamate)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Marine pollutant: Yes  
 Limited quantity: 5 L / 30 kg  
 Excepted quantity: E1  
 EmS: F-E, S-E

**Air transport (ICAO)**

**14.1. UN number:** UN 1263  
**14.2. UN proper shipping name:** Paint related material  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: yes



#### **14.6. Special precautions for user**

Handle in accordance with good industrial hygiene and safety practices.

#### **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

The transport takes place only in approved and appropriate packaging.

---

### **SECTION 15: Regulatory information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

2004/42/EC (VOC): 401 g/l

##### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

#### **15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

---

### **SECTION 16: Other information**

#### **Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

**TIP TOP COROPUR AKTIVATOR A-1949**

Revision date: 25.11.2015

Revision No: 1,1

Product code: 00359-1228



---

**Relevant H and EUH statements (number and full text)**

H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Further Information**

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*